



## PRODUCT INFORMATION

LVT - 5.0mm Overall Thickness / 20mil Wear Layer  
Glue Down  
Plank Size – 9” x 60” (Nominal)  
22.5 SqFt / Carton – 6 Pieces / Carton  
60 Cartons / Pallet  
Enhanced UV Urethane Coating  
Fiber Glass Core  
Top Embossed Textured - 100% Virgin Material  
True Matte Finish  
Commercial  
Full Spread Glue Down Only  
25 Year Residential Limited Warranty  
10 Year Light Commercial Limited Warranty



### COLORS:

Autumn Oak	LAYFAUOA	Maine Walnut	LAYFMAWA
Bog Oak	LAYFBOOA	Post Oak	LAYFPOOA
Full Oak	LAYFFUOA	Shadow Grey	LAYFSHGR
Home Oak	LAYFHOOA	Western Oak	LAYFWEOA

## WARRANTY INFORMATION

### 25 Year Limited Residential Warranty

We warrant that your flooring will be free from manufacturing defects for a period of 25 years following the date of purchase and under normal household conditions will not wear out, or delaminate.

### 10 Year Limited Light Commercial Warranty

We warrant for a period of 10 years following the date of purchase that your flooring will be free from manufacturing defects under light commercial use. Correctly constructed wood subfloors should not transmit moisture. Mold and mildew growth caused by moisture is not covered. "Light commercial use" is defined as environments which do not have heavy commercial use but do have adequate control of interior temperature and humidity.

### FLOOR MAINTENANCE

- Use floor protectors under furniture.
- Use walk off mats at entrances to prevent dirt and grit from being tracked on to the floor.
- Sweep or vacuum the floor regularly to remove loose dirt. Do NOT use vacuums that use a beater bar or turn beater bar off.
- Clean up spills immediately.
- Damp mop as needed using clean water and a diluted floor cleaner suitable for LVT. Do NOT use harsh cleaners or chemicals on the floor. Do NOT use abrasive scrubbing tools. Do NOT use detergents, abrasive cleaners or "mop and shine" products. Do not use steam mops.