



## PRODUCT INFORMATION

SPC - 5.5mm Overall Thickness /20mil Wear Layer

Attached Underlayment

Plank Size – 7" x 48" (nominal)

24.292 SF / Carton - 10 Pieces / Carton

65 Cartons / Pallet

Angle / Angle Locking System


4 Sided Painted Bevel Edge

AC5 Rating

Embossed Texture

Water Resistant - 100% Virgin Material

25 Year Residential Limited Warranty



## PLANK COLORS

Amber NATGEAMBEAA

Topaz NATGETOPAAA

Calcite NATGECALCAA

Ziron NATGEZIRCAA

## WARRANTY INFORMATION

### 25 Year Limited Residential Warranty

We warrant that your flooring will be free from manufacturing defects for a period of 25 years following the date of purchase and under normal household conditions will not wear out, or delaminate.

### 10 Year Limited Light Commercial Warranty

We warrant for a period of 10 years following the date of purchase that your flooring will be free from manufacturing defects under light commercial use. Correctly constructed wood subfloors should not transmit moisture. Mold and mildew growth caused by moisture is not covered. "Light commercial use" is defined as environments which do not have heavy commercial use but do have adequate control of interior temperature and humidity.

## FLOOR MAINTENANCE

- Use floor protectors under furniture.
- Use walk off mats at entrances to prevent dirt and grit from being tracked on to the floor.
- Sweep or vacuum the floor regularly to remove loose dirt. Do NOT use vacuums that use a beater bar or turn beater bar off.
- Clean up spills immediately.
- Damp mop as needed using clean water and a diluted floor cleaner suitable for SPC. Do NOT use harsh cleaners or chemicals on the floor. Do NOT use abrasive scrubbing tools. Do NOT use detergents, abrasive cleaners or "mop and shine" products. Do not use steam mops.